



Breedon Easyflow Screed

Ideal for:

- Internal finished floors
- Under floor heating systems
- Bonded and unbonded and floating floors



Breedon Easyflow Screed

Technical Data

Breedon Easyflow Screed is a quality assured free flowing floor screed specifically designed to meet the requirements of BS EN 13813:2002

Our Easyflow screed is a quality assured flowing screed designed specifically for interior applications that requires minimum compaction and will produce a level floor ready to receive tiles, carpets, paints ect.

It is ideally suited to under floor heating systems.

Breedon Easyflow screed is suitable for most types of construction, including new build and renovation work – bonded, unbonded and floating.

Breedon Easyflow screed is supplied to specialist, trained contractors who have been approved by Breedon Aggregates to ensure that the final product is durable, flat and smooth.

The benefits are:

- Increased productivity
- Up to 200 m² may be achieved in one day
- Reduced thickness
- Earlier trafficking
- Improved Finish
- No long term curing required
- Low shrinkage
- Improved surface regularity (SR2 or better)
- Curling eliminated
- Excellent for under floor heating systems.

Thickness and Drying Times:

Breedon Easyflow screed has a significantly improved flexural strength over cementitious screeds and therefore may be laid thinner than most conventional screeds, with typical floor thicknesses of 35mm rather than the standard 75mm.

Using Easyflow screeds significantly reduces the drying times allowing faster access for the final floor covering.

For further details on this and other products available contact:

Eastern England (Stamford)

Telephone 01780 482 000

Eastern England (Grimsby)

Telephone 01472 351987